

0275 SERIES



2.54x2.54mm(0.1"x0.1"), Pin Header, Dual Row, 7.4mm Base, Straight.

Specifications

Current Rating: 3 Amp

Insulation Resistance: 500 MΩ Min.

Dielectric Withstanding: 600 VAC

Contact Resistance: 20 mΩ Max.






Operating Temperature: -40°C to +105°C

Materials

Contact Material: Copper Alloy

Contact Plating: Gold/Tin over Nickel

Insulator: Glass Filled Polyester



No. of Pins/Row	Dimension Information	
	C	D
-	-	-
04	7.62	10.16
05	10.16	12.70
06	12.70	15.24
07	15.24	17.78
08	17.78	20.32
09	20.32	22.86
10	22.86	25.40
11	25.40	27.94
12	27.94	30.48

No. of Pins/Row	Dimension Information	
	C	D
13	30.48	33.02
14	33.02	35.56
15	35.56	38.10
16	38.10	40.64
17	40.64	43.18
18	43.18	45.72
19	45.72	48.26
20	48.26	50.80
21	50.80	53.34
22	53.34	55.88
23	55.88	58.42

No. of Pins/Row	Dimension Information	
	C	D
24	58.42	60.96
25	60.96	63.50
26	63.50	66.04
27	66.04	68.58
28	68.58	71.12
29	71.12	73.66
30	73.66	76.20
31	76.20	78.74
32	78.74	81.28
33	81.28	83.82
34	83.82	86.36

No. of Pins/Row	Dimension Information	
	C	D
35	86.36	88.90
36	88.90	91.44
37	91.44	93.98
38	93.98	96.52
39	96.52	99.06
40	99.06	101.60

Ordering Information

0275 - X 2 1 - X X 0

1: Tin

2: Gold

3: Half Gold

Position